

# COMMERCIAL DEHUMIDIFIER

## FRAL FSW 63

### 63 LITRES PER DAY

This is the latest addition to the Fral “Corrosive Environment” range. These specialised dehumidifiers can handle the toughest conditions including heated indoor swimming pools; scientific laboratories; manufacturing facilities and basically anywhere corrosive elements are present.

Elegant lines, quiet and powerful, these commercial dehumidifiers carry the Fral name with pride.

#### Features:

- Pump for lifting condensed water
- Two speed fan
- Digital control of humidity and defrost
- Digital display
- Protection IPX22
- Low noise
- Low power consumption
- Rotary compressor
- Power supply 220-240V 50Hz



#### CONDENSED WATER AT DIFFERENT AMBIENT TEMPERATURE AND HUMIDITY CONDITIONS

10°C 60%	10°C 80%	15°C 60%	15°C 80%	20°C 60%	20°C 80%	25°C 60%	25°C 80%	27°C 65%	27°C 80%	30°C 80%	32°C 90%
10 l/d	18 l/d	15 l/d	23 l/d	20 l/d	28 l/d	25 l/d	35 l/d	28 l/d	39 l/d	52 l/d	63 l/d

#### TECHNICAL DATA

Power Consumption (at 27°C, 65% rh)	700 w
Power Consumption (at 35°C, 95% rh)	950 w
Absorbed Current (at 35°C, 95% rh) standard ver.	4.4 A
Start Current Full Load Amp	20 A
Air Flow	600 cm/h
Noise level (at 3 meters)	49 dB
Refrigerant	R407c
Defrosting Control	Electronic
Continuous Drainage Pipe (male)	19mm
Temperature Range standard version	7-35° C
Relative Humidity Range	45-99%
Condensation Capacity (at 26°C, 60% rh)	52 l/24 hr
Condensation Capacity (at 32°C, 90% rh)	63 l/24 hr
Weight	48 kg
Dimensions	78cm x 68cm x 25cm

