

Model	Power Consump. (20°C, 60% rh)	Power Consump. (35°C, 95% rh)	Absorbed Current (35°C, 95% rh) standard version	Locked Rotar Current LRA standard version 230/1/50	Air Flow	Noise Level (at 3 mtrs)	Refrig.	Standard Defrost Control System	Hot Gas Defrost Control System (otional)	Water Tank Cap.	Cont. Drain Pipe Connect	Temp. Range standard version	Temp. Range hot gas defrost version	Relative Humidity Range	Conden. Capacity (30°C, 80% rh)	Conden. Capacity (32°C, 90% rh)	Power	Weight	Dimensions
FDNF33	420 w	580 w	3.3 A	18	380 cm/h	43 dB	R134a	Electronic	Electronic thermostat	8 kg	25mm	7-35°C	1-35°C	35-99%	26 l/24 hr	33 l/24 hr	220-240V, 50 Hz	32 kg	70cm x 37cm x 35cm
FDNF44	530 w	780 w	4 A	18	400 cm/h	43 dB	R134a	Electronic	Electronic thermostat	9 kg	25mm	7-35°C	1-35°C	35-99%	36 l/24 hr	44 l/24 hr	220-240V, 50 Hz	38 kg	72cm x 37cm x 35cm
FDNF62	700 w	950 w	4.4 A	20	650 cm/h	51 dB	R134a	Electronic	Electronic thermostat	12 kg	25mm	7-35°C	1-35°C	35-99%	52 l/24 hr	62 l/24 hr	220-240V, 50 Hz	44 kg	77cm x 45cm x 41cm
FDNF96	980 w	1350 w	7.2 A	29	1000 cm/h	52 dB	R134a	Electronic	Electronic thermostat	15 kg	25mm	7-35°C	1-35°C	35-99%	80 l/24 hr	96 l/24 hr	220-240V, 50 Hz	52 kg	90cm x 55cm x 41cm
FD160	1950 w	2300 w	12 A	33		54 dB	R407c	Electronic	Electronic Thermostat		19 mm	7-35°C	0.5-35°C	45-99%	130 l/24 hr	160 l/24 hr	220-240V, 50 Hz	66 kg	980cm x 682cm x 530cm
FD240	2900 w	3500 w	6 A	28		55 dB	R407c	Electronic	Electronic Thermostat		19 mm	7-35°C	0.5-35°C	45-99%	190 l/24 hr	240 l/24 hr	3 Phase	72 kg	980cm x 682cm x 530cm
FD360	4500 w	5800 w	11 A	50		61 dB	R407c	Electronic	Electronic Thermostat		19 mm	7-35°C	0.5-35°C	45-99%	300 l/24 hr	360 l/24 hr	3 Phase	150 kg	118cm x 90cm x 71cm
FD520	5800 w	6500 w	16 A	75		65 dB	R407c	Electronic	Electronic Thermostat		19 mm	7-35°C	0.5-35°C	45-99%	420 l/24 hr	520 l/24 hr	3 Phase	190 kg	118cm x 90cm x 71cm
FD750	9000 w	11000 w	22 A	80		67 dB	R407c	Electronic	Electronic Thermostat		19 mm	7-35°C	0.5-35°C	45-99%	600 l/24 hr	750 l/24 hr	3 Phase	230 kg	200cm x 130cm x 160cm
FD980	11200 w	13000 w	28 A	100		70 dB	R407c	Electronic	Electronic Thermostat		19 mm	7-35°C	0.5-35°C	45-99%	870 l/24 hr	980 l/24 hr	3 Phase	320 kg	200cm x 130cm x 160cm

Model	Power Consump. (27°C, 65% rh)	Power Consump. (35°C, 95% rh)	Absorbed Current (35°C, 95% rh) standard version	Locked Rotar Current LRA standard version 230/1/50	Air Flow	Noise Level (at 3 mtrs)	Refrig.	Standard Defrost Control System	Hot Gas Defrost Control System (otional)	Water Tank Cap.	Cont. Drain Pipe Connect	Temp. Range standard version	Temp. Range hot gas defrost version	Relative Humidity Range	Conden. Capacity (30°C, 80% rh)	Conden. Capacity (32°C, 90% rh)	Power	Weight	Dimensions
FSW63	700 w hard wired	950 w hard wired	4.4 A	20	600 cm/h	49 dB	R407c	Electronic			19 mm	7-35°C		45-99%	52 l/24 hr	63 l/24 hr		48 kg	78cm x 68cm x 25cm
FSW96	980 w hard wired	1350 w hard wired	7.2 A	29	800 cm/h	49 dB	R407c	Electronic			19 mm	7-35°C		40-99%	80 l/24 hr	96 l/24 hr		72 kg	175cm x 50cm x 29cm